

SL3731D

电脑直驱钉扣机

Computerized Direct Driving Button Attaching Sewing Machine



自动送扣装置 Auto Feed Button Machine





SL3731D

SL -3730D	SL-3731D	SL-3732D	SL -3733D	SL -3735D	SL -3736D	SL -3737D	SL-3738D	SL-3739D
		大衣扣 Overcoat button	有余线大衣扣 Spare line overcoat button	立扣 Stand button	雨伞珠子 Umbrella	印染吊线四针 Coiling	西服仿手工绕线	袜子标签专用 Socks label

产品特点 Function & Specification:

- Strong applicability, suitable for direct drive / computer sewing machine as 373, 438, 1373, 1903.
- Easy to install, just need to connect 2 cables to start working, with up and down adjustment function.
- Greater functionality: four-hole, two-hole and three-hole non-standard buttons, sewing range 8~28mm, special customized machine sewing range up to 5~ 35mm.
- The button clamp is directly controlled by the imported cylinder, the reaction is sensitive, and the size is adjustable, suitable for different types of buttons.
- The vibrating plate is stamped and formed by special materials. It has strong vibration transmission capability, accurate identification of the front and back of the button, and has a start-stop function, Adopt induction protection device, the light is on when the buckle is closed, and the light is off when the buckle is opened sewing protection function, longer service life and more power saving.
- Cylinder drive type, sensitive, easy to adjust, 15% more efficient than traditional models.
- Each machine comes standard with 14 kinds of button positioning claw mounting plates, which can be replaced according to different buttons, and only need two screws for easy replacement.
- Using a 7-inch capacitive display, can display Chinese, English, Vietnamese three languages. Faster response and smooth operation.

- 适用能力强,适配直驱/电脑373, 438, 1373, 1903。
- 安装方便只需2根连接线就可以使用,设有上下调节功能。
- 功能强大: 四孔, 二孔以及三孔等非标准的纽扣, 缝制范围8~28mm, 特殊定 做的机器缝制范围可达5~35mm。
- 扣夹采用进口气缸直接控制,反应灵敏,且大小可调,适用不同类型的纽扣。
- 振动盘采用特殊材料一次性冲压成型,震动传导能力强,纽扣正反面识别准确, 设有起停功能,缝制保护功能,采取感应保护装置,扣夹闭合时灯亮起,扣夹 张开时灯熄灭使用寿命更长,更加省电。
- 采用气缸传动式,反应灵敏,调节方便,比传统机型的效率提高了15%。
- 每台机器标配14种纽扣定位爪安装板,可根据不同的纽扣进行更换,且只需两 个螺丝,更换方便。
- 采用7英寸的电容显示屏,可显示中文,英文,越南文三种语言。反应更快,操 作流畅。

Contact