



SL-120ABF-CM

全自动送扣装置 (带相机/图案识别)

Automatic button feeder with camera (for logo positioning)



1. Button machine with this device is high efficiency, is the artificial machinery of the deduction machine more than 3 times, Automatic delivery system can choose positive and negative (non-standard can be customized), each time to send Deduction time of 0.5 seconds, about 120 times per minute to send buck, the button system easy to Jane Single, a key to get.

2. Button applicable range 8mm-30mm, four holes, two holes.

3. This button can be equipped with 1903 series, 438 series, 373 series, 4-2 series Columns and other models, the application of strong performance.

1. 钉扣机配此装置效率高, 是人工机械式钉扣机的3倍以上, 全自动送扣系统可以选定正反面(非标可定做), 每次送扣时间为0.5秒, 每分钟送扣120次左右, 输钮系统方便简单, 一键搞定。

2. 纽扣适用范围8mm-30mm, 四孔位, 两孔位。

3. 此送扣装置可通配1903系列, 438系列, 373系列, 4-2系列等各种机型, 适用性能强。

Model No.	Machine head	Needle	Needle No	Button sewing speed pcs/minute	Button feeding speed pcs/minute	Machine speed RPM	Presser foot height mm	Button Diameter mm	Button thickness mm	Air pressure	Voltage	Rated power	Button feed stability	Packing size	G.W
SL-120ABF-CM	Device only			40-50	60-65			6-28	1-5	0.25-0.30	VAC110/220V±10%; 50/60Hz	65W	99.7%	580*550*460mm	32kg
	1903D	DP*17-14号	1	40-50	60-65	2600	12	6-28	1-5	0.25-0.30	VAC110/220V±10%; 50/60Hz	600W+65W	99.7%	1250*750*1220mm	132kg
	438D	DP*17-14号	1	40-50	60-65	2600	12	6-28	1-5	0.25-0.30	VAC110/220V±10%; 50/60Hz	600W+65W	99.7%	1250*750*1220mm	132kg
	373D	TQ*1-14号	1	40-50	60-65	1500	13	6-28	1-5	0.25-0.30	VAC110/220V±10%; 50/60Hz	550W+65W	99.7%	1250*750*1220mm	112kg
	1377D	TQ*1-14号	1	40-50	60-65	1500	13	6-28	1-5	0.25-0.30	VAC110/220V±10%; 50/60Hz	550W+65W	99.7%	1250*750*1220mm	112kg



AI intelligent camera



Equipped with a computer system



7.3 inch touch pad penal



373D/1377D



1903D



430D

Contact